




	PRODUCT CHARACTERISTICS			
	Standard	Requirement	Unit	Results
PRODUCT DESCRIPTION				
Surface treatment	-	-	-	Protocolsol <small>TRIPLE ACTION DURABILITY</small>
Surface complex	-	-	-	D-Max
Foam	-	-	-	
Thickness	EN 428	-	mm	2,1
Weight	EN 430	-	kg/m ²	2,9
Length	EN 426	-	lm	26.4 max
Width	EN 426	-	lm	1,5
SPORT PROPERTIES				
Shock absorption	EN 14808	≥ 25	%	-
Vertical deformation	EN 14809	≤ 3.5	mm	-
Energy return	NF P 90 203	≥ 0.31	m/s	-
Sliding coefficient	EN 13036-4	80 to 110	-	80 - 110
Ball bounce	EN 12235	≥ 90	%	≥ 90
Ball speed	UEFA	50 to 65	cm	-
	ITF	-	-	-
TECHNICAL CHARACTERISTICS				
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 350
Impact resistance	EN 1517	≥ 8	N/m	≥ 8
Indentation resistance	EN 1516	≤ 0.5	mm	≤ 0.5
CLASSIFICATION				
Fire	EN 13501-1	-	-	 Bfl-s1
Anti-bacterial activity (E. coli - S. aureus - MRSA) (3)	ISO 22196	-	-	> 99 % inhibits growth
DECLARATION OF PERFORMANCE				
	DOP n°xxx	-	-	Fire Shock Absorption Sliding Coefficient Abrasion Resistance Resistance to rolling load

	INSTALLATION METHODS		
	Gerflor's recommendation	Unit	Results
Glued installation: "Original"	Level of dampness of the subfloor	%	RH < 80% (BS 8203) or < 4.5% humidity (CCM)

COLOUR RANGE						
						Customized lengths
6381 Maple Design	6375 Oak Design	6211 Gold	6038 Terracotta	6159 Pink	6146 Coral	
						
6180 Red	6559 Spring	6557 Forest	6570 Mint Green	2404 London Light Blue	6445 Lagoon	6430 Blue
						
6431 Teal	6758 Silver Gray	6873 Anthracite	3764 Taupe	6347 Beige	6830 Black	

(3) The implementation of an effective cleaning method is the best defence against infection

